

**Manufacturer: Jacksons Fencing**

**Web: [www.jacksons-security.co.uk](http://www.jacksons-security.co.uk)**

**Tel: +44 (0)1233 750393 | 0800 953 3699**

**Product Reference: METAL PLAYTIME® FENCING**

## **Service Life of Fencing**

Metal fencing and gates designed and manufactured to be fit for purpose and providing a minimum 25 year guarantee, delivering the lowest whole life cost and significantly reduced carbon footprint.

## **Fencing & Posts:**

1000mm High, Post Dimensions: 60 x 60mm (3000mm Post Centres)

## **Panel Construction:**

1000mm high (nominal height) panels have two horizontal rectangular hollow section rails 60 x 40mm; walls 2mm thick, with 25 x 25mm pales.

## **Posts:**

Posts are rectangular hollow section steel hot dip galvanised inside and out to BS EN 1461 as standard.

## **Fixings:**

Fence panels are fixed to posts using hidden vandal-proof panel to post connectors.

## **Finish / Colour:**

Hot dip galvanised to BS EN ISO 1461 as standard

## **Setting Posts**

Holes: Excavate neatly and with vertical sides.

Setting posts as standard in concrete: To BS 8500-2.

[Mix: Designated concrete not less than GEN1 or Standard prescribed concrete not less than ST2.] [Alternative mix for small quantities: 50kg Portland cement to 150kg fine aggregate to 250kg, 20mm nominal maximum size coarse aggregate, medium workability.] [Admixtures: Do not use]

Filling: Position post/strut and fill hole with concrete to not less than the specified depth, well rammed as filling proceeds and consolidated. Backfilling of holes not completely filled with concrete: Excavated material, well rammed and consolidated.

## **NOTES:**

For more information please contact Jacksons Fencing. We reserve the right to alter specification within this document at any time.