

Manufacturer: Jacksons Fencing

Web: www.jacksons-security.co.uk

Tel: +44 (0)1233 750393 | 0800 953 3699

Product Reference: TIMBER PLAYTIME® FENCING

Service Life of Fencing

Timber fencing and gates designed and manufactured to be fit for purpose and providing a minimum 25 year guarantee, delivering the lowest whole life cost and significantly reduced carbon footprint.

Fencing & Posts:

1050mm High, Post Dimensions: 120 x 120mm (3255mm Post Centres)

Panel Construction:

Timber Playtime approved by RoSPA. The panels sit above a gravel board 145 x 35 x 3.255mm long. All timber is Jakcure treated to give a 25 year guarantee.

Pale Construction:

95 x 35 x 900mm high pales with 75mm pales spacing sandwiched between two rails at the top and two rails at the bottom.

Posts:

Posts are 120mm x 120mm x 1.83m long, made from 2 x sections of 120 x 45 with a spacer between 95 x 35 x 270mm long.

Over length set in concrete

Finish / Colour:

Natural Jakcure® finish as standard

Multi coloured pales (yellow, red and blue)

Setting Posts

Holes: Excavate neatly and with vertical sides.

Setting posts as standard in concrete: To BS 8500-2.

[Mix: Designated concrete not less than GEN1 or Standard prescribed concrete not less than ST2.] [Alternative mix for small quantities: 50kg Portland cement to 150kg fine aggregate to 250kg, 20mm nominal maximum size coarse aggregate, medium workability.] [Admixtures: Do not use]

Filling: Position post/strut and fill hole with concrete to not less than the specified depth, well rammed as filling proceeds and consolidated. Backfilling of holes not completely filled with concrete: Excavated material, well rammed and consolidated.

NOTES:

For more information please contact Jacksons Fencing. We reserve the right to alter specification within this document at any time.