

Cleft Chestnut

Jacksons Fencing



Simple, fast, and cost effective demarcation solution, our Cleft Chestnut fencing is assembled using best quality galvanised wire.

- Galvanised 14 guage 2mm wire with 4 strands per row
- Pales are cleft, peeled and pointed at one end
- Approximate spacing between pales in 75mm with approximately 9 pales per metre
- All posts, struts and anchor supports are Jakure® treated and guaranteed for 25 years
- This Chestnut fencing is not Jakure® treated timber as Chestnut is a hardwood and therefore cannot be guaranteed for 25 years

Specification

Two Styles of Chestnut fencing available. Style A has 2 rows of wire, Style B has 3 rows of wire.

Fence Height

Style A - 0.90m high 9.10m rolls
Style A - 1.10m high 9.10m rolls

Style B - 0.90m high 9.10m rolls
Style B - 1.10m high 9.10m rolls
Style B - 1.20m high 4.55m rolls
Style B - 1.40m high 4.55m rolls
Style B - 1.50m high 4.55m rolls
Style B - 1.80m high 4.55m rolls



Style A



Style B

Corner and End Posts (not Chestnut)

Machine round 100mm diameter. Use at maximum 45m intervals or corners and changes in direction.

Fence height	Post height
0.90m and 1.10m	1.50m
1.20m and 1.40m	1.80m
1.50m	2.10m
1.80m	2.40m

Struts (not Chestnut)

Machine round 60mm diameter. Use one on end posts and two on corner and intermediate straining posts

Fence height	Post length
0.90m and 1.10m	1.35m
1.20m and 1.40m	1.80m
1.50m	2.10m

Anchor Stakes (not Chestnut)

Half Round with minimum of 75mm face, pointed and peeled. One per 750 - 900mm

Intermediate Posts (not Chestnut)

Machine round, 75mm diameter. Use at 2.70m intervals

Fence height	Post length
0.90m and 1.10m	1.50m
1.20m	1.65m
1.40m	1.80m
1.50m	2.10m
1.80m	2.40m

View our website for Q40 specification documents, CAD drawings and products available to buy online.

A fully made to measure service is available. All Jacksons Fencing systems and gates may be designed and manufactured to suit site conditions.