

Traditional Featherboard Fencing

Manufacturer: Jacksons Fencing.
Web: www.jacksons-fencing.co.uk.
Tel: +44 (0)1233 750393.

All materials are covered by the Jacksons 25-year guarantee. On timber products, **only** the unique Jakcure® treatment process delivers a 25-year guarantee against all wood boring pest and all forms of dry and wet rot. On steel fencing, the exclusive Jacksons 25-year Service Life guarantee provides cover against defects such as design, manufacturing finish and fitness for purpose .

Product reference: Traditional Featherboard Fencing.

•Posts:

[230100]. - 1800 mm, 125 x 100 section for fence 1200 mm high.
[230200]. - 2400 mm, 125 x 100 section for fence 1500 mm high.
[230300]. - 2700 mm, 125 x 100 section for fence 1800 mm high.

•Corner posts:

[Not required].
[230800]. - 1800 mm, 125 x 125mm section for fence 1200 mm high.
[230900]. - 2400 mm, 125 x 125mm section for fence 1500 mm high.
[231000]. - 2700 mm, 125 x 125mm section for fence 1800 mm high.

•Pales:

[230400]. - 1050 mm for fence 1200mm high used with gravel board. (29 per 2400 mm bay).
[230500]. - 1350 mm for fence 1500mm high used with gravel board. (29 per 2400 mm bay).
[230600]. - 1650 mm for fence 1800mm high used with gravel board. (29 per 2400 mm bay).
[232300]. - 900 mm, used without gravel board. (29 per 2400 mm bay).
[232400]. - 1200 mm, used without gravel board. (29 per 2400 mm bay).
[232500]. - 1500 mm, used without gravel board. (29 per 2400 mm bay).
[232600]. - 1800 mm, used without gravel board. (29 per 2400 mm bay).

•Rails::

[231400]. - 2400 x 38 x 87mm weathered top.

-Gravel Boards:

[230700]. - 2400 x 150 x 25mm.

•Gates:

[231100]. - 1150 x 1000 mm, for fence 1200 mm high, complete with hinges and catch.
[231200]. - 1450 x 1000 mm, for fence 1500 mm high, complete with hinges and catch.
[231300]. - 1750 x 1000 mm, for fence 1800 mm high, complete with hinges and catch.
[231900]. - 1750 x 900 mm, for fence 1800 mm high, complete with hinges and catch.
[232000]. - 1900 x 1000 mm, for fence 1950 mm high, complete with hinges and catch.

•Accessories:

[None].

[Jakcured end grain preservative]. - Required to post treatment cutting or drilling.

Pales are taper sawn, which are 150 mm shorter than the height of the fence and stand on gravel boards as standard.

Jacksons Fencing
NBS Specification

Features:

- Matching gates available.
- Posts: 125 x 100 mm section for extra strength.

Installation

In accordance to manufacturers instructions