

Jacksons Fencing Specification Sheet

Cleft Chestnut Fencing

- All timber used to manufacture the posts, struts and anchor posts are Jakcured softwood guaranteed for 25 years
- Best galvanized 2mm wire strands used to assemble chestnut fencing
- Four strands per row for extra strength
- Pales are cleft, peeled and pointed one end
- Approximate spacing of pales 75mm

Please note this chestnut fencing is **NOT** Jakcured timber.

Our fencing is assembled with the best galvanized 14 gauge (2mm) wire, 4 strands per row. Pales are cleft, peeled and pointed one end. Approximate spacing of pales 75mm.



Specification

Fence Height

Style 'A' 9.1m rolls	0.9m	1.1m			
Style 'B' 9.1m rolls	0.9m	1.1m			
Style 'B' 4.55m rolls	1.2m	1.4m	1.5m	1.8m	

Corner and End Posts

Machine rounded 100mm diam. Use at maximum 45m intervals or corners and change in direction.

0.9m and 1.1m	1.5m
1.2m and 1.4m	1.8m
1.5m	2.1m
1.8m	2.4m

Struts

Machine rounded. 60mm diam. Use one on end posts and two on corner and intermediate straining posts.

0.9m and 1.1m	1.4m
1.2m and 1.4m	1.8m
1.5m	2.1m
1.8m	2.4m

Intermediate Posts

Machine round 75mm diameter use at 2.7m intervals

Fence height	Post length
0.9m	1.5m
1.1m	1.5m
1.2m	1.65m
1.4m	1.8m
1.5m	2.1m
1.8m	2.4m

Anchor Stakes

Half round with minimum of 75mm face, pointed and peeled. One per strut 750 - 900mm



Style A (2 rows of wire)



Style B (3 rows of wire)

Register on the website to gain access to Q40 specification documents and CAD drawings. A fully made to measure service is available. All Jacksons fencing systems and gates maybe designed and manufactured to suit site conditions.