DRB reviewed RHJ 11/05/2011 JFT/MKT/SPC/0511/V2



## **Entrance Gates**

- All timber used throughout is superior quality Jakcured softwood guaranteed for 25 years
- The timber is machined to a standard size, stop chamfered and planed
- All rail and cross bracings are bolted with stainless steel bolts
- All joints are morticed and tennoned
- Traditional attractive designs
- Supplied in natural Jakcured finish



Detail of curved hanging stil



Double wide entrance gate, supplied in natural Jakcured finish

## **Specification**

## **Entrance Gates Wide**

Gates are 1.2m high except for the hanging stile which is 1.5m Gate widths are from 1.8m to 3.6m

Hanging Stile 125 x 75mm, Slam Stile 75 x 75mm

Top rail is 100 x 75mm

Under rail and cross braces 75 x 25mm

Right hand hanging as standard when viewed from the front, left hand hanging is also available

Additional items required for hanging a single wide entrance gate Galvanized fittings, Hinge set, Spring catch fitted, Anti-lift device, Padlock, 2.1m 175 x 175mm hanging post, 2.1m 150 x 150mm shutting post.



Entrance gate wide, supplied in natural Jakcured finish

## **Entrance Gates Narrow**

Gates are 1.2m high except for the curved hanging stile which is 1.5m Gate widths are from 0.9m to 1.5m

Slam Stile 75 x 75mm

Top rail is 100 x 75mm

Single crossed braced

Left hand hanging as standard when viewed from the front, right hand hanging is also available

Additional items required for hanging a single narrow entrance gate Galvanized fittings, Hinge set, Spring catch fitted, anti-lift device, padlock, two 2.1m 150 x 150mm gate posts.



Entrance gate Narrow painted white

Register on the website to gain access to Q40 specification documents and CAD drawings. A fully made to measure service is available. All Jacksons fencing systems and gates maybe designed and manufactured to suit site conditions.

