

Entrance Gates

Manufacturer: Jacksons Fencing. Web: www.jacksons-fencing.co.uk. Tel:+44 (0)1233 750393.

All materials are covered by the Jacksons 25-year guarantee. On timber products, **only** the unique Jakcure® treatment process delivers a 25-year guarantee against all wood boring pest and all forms of dry and wet rot. On steel fencing, the exclusive Jacksons 25-year Service Life guarantee provides cover against defects such as design, manufacturing finish and fitness for purpose .

Product reference: Entrance Gates.

```
Type:
```

[262800]. - Narrow gate, 900 mm wide x 1200 mm high. 1500mm at highest point. [262900]. - Narrow gate, 1200 mm wide x 1200 mm high. 1500mm at highest point

[263000]. - Narrow gate, 1500 mm wide x 1200 mm high. 1500 mm at highest point.

point. [263100]. - Wide gate, 1800 mm wide x 1200 mm high. 1500 mm at highest point. [263200]. - Wide gate, 2100 mm wide x 1200 mm high. 1500 mm at highest point [263300]. - Wide gate, 2400 mm wide x 1200 mm high. 1500 mm at highest point. [263400]. - Wide gate, 2700 mm wide x 1200 mm high. 1500 mm at highest point. [263500]. - Wide gate, 3000 mm wide x 1200 mm high. 1500 mm at highest point. [263600]. - Wide gate, 3300 mm wide x 1200 mm high. 1500 mm at highest point. [263700]. - Wide gate, 3600 mm wide x 1200 mm high. 1500 mm at highest point.

-Hanging:

[Left handed]. [Right handed].

•Fixing:

[TRHSDL]. - Kit for double wide gate. Hinge, latch and posts.

[TRHSSL]. - Kit for single wide gate. Hinge, latch and posts.

[TRHSSLN]. - Kit for single narrow gate. Hinge, latch and posts.

- Operation:

[Automatic]. Gate Safe compliant: EN 13241-1:2003 (EN 12453:2003 / EN 12445:2000 / EN 12978:2003 / EN 12604:2000 / EN 12605:2000)
[Manual].

Options

Type:

- Narrow entrance gates, 1200 mm high:

900-1500 mm wide.

- Wide entrance gates, 1200 mm high:

1800–3600 mm wide.

Fixing:

 TRHSSL: Hanging kit includes: Galvanized fittings, hinge set, spring catch fitted, antilift device, padlock and 2100 mm, 175 x 175 mm hanging post and 150 x 150 mm closing post.



Jacksons Fencing

NBS Specification

- TRHSDL: Hanging kit for double-wide entrance gate, including posts, hinges, anti-lift devices, padlocks and loop over, drop bolt and centre gate stop.
- TRHSSLN: Galvanized fittings, hinge set, spring catch fitted, anti-lift device, padlock and two 2100 mm, 150 x 150 mm gate posts.

Timber entrance gates available in either narrow or wide format.

Features:

- Timber is machined to a standard size, stop chamfered and planed.
- All joints are mortised and tenoned or dowelled.
- All rail and cross bracings are bolted with stainless steel bolts.

All timber used throughout is superior quality Jakcured softwood guaranteed for twenty five years.

Installation

In accordance to manufacturers instructions