

Hit and Miss Panel

Manufacturer: Jacksons Fencing.
Web: www.jacksons-fencing.co.uk.
Tel: +44 (0)1233 750393.

All materials are covered by the Jacksons 25-year guarantee. On timber products, **only** the unique Jakcure® treatment process delivers a 25-year guarantee against all wood boring pest and all forms of dry and wet rot. On steel fencing, the exclusive Jacksons 25-year Service Life guarantee provides cover against defects such as design, manufacturing finish and fitness for purpose .

Product reference: Hit and Miss Panel.

•Type:

[631500]. - Horizontal, 910 mm high.
[631600]. - Horizontal, 1220 mm high.
[631700]. - Horizontal, 1520 mm high.
[634000]. - Horizontal, 1830 mm high.
[634010]. - Convex, 1830 mm high.
[634110]. - Convex, 1520 mm high.
[634210]. - Convex, 1220 mm high.
[634310]. - Convex, 910 mm high.
[634100]. - Vertical, 1520 mm high.
[634200]. - Vertical, 1220 mm high.
[634300]. - Vertical, 910 mm high.

-Gravel boards:

[Not required].
[Required].

•Gate:

[Not required].
[631800]. - Horizontal, right handed. 1750 mm high, complete with hinges and latch.
[631880]. - Horizontal, left handed. 1750 mm high, complete with hinges and latch.
[631900]. - Vertical, right handed. 1750 mm high, complete with hinges and latch.
[631990]. - Vertical, left handed. 1750 mm high, complete with hinges and latch.

As standard

Size:

Panels are 1830 mm wide, framing 45 x 50 mm, recessed to take boards, 95 x 8 mm with internal battens 50 x 12 mm.

Options

Gate:

Width: 1000 mm. Available in either left or right hand hanging includes galvanized hinges and ring latch.

Other sizes also available.

Hit and Miss vertical and horizontal:

- Designed for use with slotted Jakposts.
- Morticed and tenoned frame for extra strength.
- Hit and Miss panels' design allows some wind to pass through - less wind resistance.
- All fixings are stainless steel.
- All timber is planed all round.

Jacksons Fencing

NBS Specification

- Visual appearance is the same from both sides.

Hit and Miss convex panel:

Elegant curved topped panel in a choice of heights. Panels are fully framed with 50 mm top and bottom rail and 45 mm side rail. Can be erected with or without gravel boards.

All timber used throughout is superior quality Jakcured softwood guaranteed for twenty five years.

Installation

In accordance to manufacturers instructions