

Jacksons Fencing Specification Sheet

Post and Rail (morticed)

This attractive fencing consists of sawn square section vertical posts, with three or four horizontal square section rails, morticed into the posts. There are additional prick posts in between the posts at the mid bay point to give extra support.

- All timber used throughout is superior quality Jakcured softwood guaranteed for 25 years
- Prick posts mid bay for enhanced looks and extra support
- Posts with mortices in have special galvanized fitting embedded in top to prevent splitting
- All fixings are heavily galvanized

Specification

Allow one post and one prick post for every 2.85m of fence, plus one post for the end of the run.

Allow three rails per 2.85m run of 3-rail fence, and four rails per 2.85m of 4-rail fence.

Posts

125mm x 75mm section, weathered one way.

Mortices 38 x 100mm centred at 150mm, 530mm, 860mm and 1180mm from top of post.

Sawn finish

Length

1.8m 3 mortices

2.1m 4 mortices

Square rails

100 x 38mm section, scarfed at both ends

Sawn finish

3.0m long

Corner posts

125 x 125mm section, weathered two ways

Sawn finish

1.8m 3 mortices

2.1m 4 mortices

Prick posts

100 x 38mm section, pointed

Sawn finish

1.5m long

1.8m long

Nails

100mm galvanized wire nails allow 11kgs - for 200mm of 3-rail fence and 14kgs for 200mm of 4-rail fence



Post and rail fencing (morticed)



Detail of rails morticed into the posts and additional prick post for extra support

Register on the website to gain access to Q40 specification documents and CAD drawings.

A fully made to measure service is available. All Jacksons fencing systems and gates may be designed and manufactured to suit site conditions.

Jacksons Fencing Stowting Common Ashford Kent TN25 6BN UK

T: +44 (0) 1233 750 393 F: +44 (0) 1233 750 403

E: sales@jacksons-fencing.co.uk W: jacksons-fencing.co.uk



Jacksons
Quality that lasts
Fine Fencing, Gates and More