



# **Stile and Bridle Gates**

Manufacturer: Jacksons Fencing. Web:<u>www.jacksons-fencing.co.uk</u>. Tel:+44 (0)1233 750393.

All materials are covered by the Jacksons 25-year guarantee. On timber products, **only** the unique Jakcure® treatment process delivers a 25-year guarantee against all wood boring pest and all forms of dry and wet rot. On steel fencing, the exclusive Jacksons 25-year Service Life guarantee provides cover against defects such as design, manufacturing finish and fitness for purpose.

Product reference: Stiles and Bridle Gates.

•Type: [200700BM]. - Stile without dog gate. [201700BM]. - Stile complete with dog gate. [201800BM]. - Dog gate for attaching to existing stile. [299770BM]. - Bridle gates.

•Accessories:

(AND)
[None].
[201600]. - Stile extension handle.
[271100]. - Two way R.O.W. latch.
[Jakcure end grain preservative]. - Required to post treatment cutting or drilling.

## Options

Type:

- Stile with dog gate:

- Posts: 1800 x 125 x 75 mm morticed to take four rails.
- Rails: 1150 x 100 x 38 mm section.
- Treads: 1200 x 175 x 50 mm section.
- Tread posts: 125 x 38 mm.

The dog gate has a top rail for nailing between the posts, with holes to support the handle attached to the plywood gate, which is contained within the slides.

## - Bridle gates:

- Size (h x w): 1270 x 1800 mm.
- Hanging posts: 2100 x 150 x 150 mm, sawn finish.
- Hinge set with adjustable bottom hinge and spring catch set galvanized.

## Accessories:

- Stile extension handle: Designed to screw onto the 125 x 75 mm stile post. Hot dip galvanized with ball top, complete with screws.
- Two way R.O.W. latch: Suitable for self closing gates where disabled people need to gain access.

## Stile with dog gate:

Pull up handle operates a board which allows a dog to pass through entrance. Stile is rabbit proof, due to a solid bottom to fill the gap.

## Installation

In accordance to manufacturers instructions