



PLEASE SPECIFY HANDING  
STATE WHICH SIDE GATES ARE CLAD

<p>RIGHT HAND HANG OPENS OUT</p>	<p>LEFT HAND HANG OPENS OUT</p>
<p>RIGHT HAND HANG OPENS IN</p>	<p>LEFT HAND HANG OPENS IN</p>

INSTALLATION.

POSITION GATE BETWEEN TWO FENCE POSTS.  
REMOVE WELDMESH TO APPROX 2.1m  
ABOVE GROUND LEVEL.

NOTES.

ALL DIMENSIONS ARE IN mm (U.N.O)  
GAP UNDERNEATH GATE IS BASED  
UPON THE SITE BEING LEVEL.

MATERIALS

POST FRAME:  $\phi$ 60.3 CHS  
GATE FRAME:  $\phi$ 41.5 CHS  
TOP RAIL:  $\phi$ 41.5 CHS  
TOP RAIL:  $\phi$ 41.5 CHS

FITTINGS REQUIRED

2m STRETCHER BAR (335930) - 4 No.  
FERRULE STRAINER (342400) - 6 No.  
STRAP FOR  $\phi$ 60.3 (065011) - 10 No.  
M8 x 40 Lg BOLT, NUT & WASHER - 10 No.  
EXTRA M8 NUT - 6 No.

FINISH

GALVANISED TO BS EN ISO 1461:1999  
POWDER COATED IF REQUIRED

**JACKSONS**  
**FINE FENCING**

Stowling Common  
Near Ashford,  
KENT, TN25 6BN

Telephone : 01233 750393  
Fax: 01233 750403  
Int. Tel : +44 (0)1233 750393

This Drawing is The Property of H.S. Jackson & Son (Fencing) Ltd.  
And May Not Be Copied Or Reproduced in Any Way Without Prior Written Permission.

20/12/13 UPDATED  
06/01/06 UPDATED  
05/12/01 ORIGINAL ISSUE

Drawn JR  
Date 28/02/02  
Checked  
Size A3  
Scale 1:15  
U.O.S

TITLE SALES & INSTALLATION DRAWING FOR  
SINGLE WELDMESH TENNIS COURT GATE  
CUSTOMER  
ACK No.  
Drawing No. 05 J2/04040  
Sheet 3 of 4