

Jacksons Fencing Specification Sheet



Chain Link

Galvanized chain link - 50mm mesh

- Chain link fencing conforms to BS 1722 part 1
- Galvanizing conforms to BS EN 10223
- Line wire is supplied with each roll



			Roll height							
			0.9m	1.2m	1.4m	1.8m	2.0m	2.4m	2.75m	3.05m
Standard No. of Line wires			2	3	3	3	3	4	5	5
Wire Size	Gauge	Length								
2.5mm	12.5g	25m	✓	✓	✓	✓				
		12.5m					✓	✓	✓	
3.0mm	10.5g	25m	✓	✓	✓					
		12.5m				✓	✓	✓	✓	✓
3.55mm	9.5g	12.5m	✓	✓	✓	✓	✓	✓	✓	✓

Chain Link PVC - 50mm mesh

- Chain link fencing conforms to BS 1722 part 1
- Where plastic coated is Grade D galvanized core except 3.55/4.75mm which is Grade A galvanized core
- Green coated PVC (Black available on request)



			Roll height							
			0.9m	1.2m	1.4m	1.8m	2.0m	2.4m	2.75m	3.05m
Standard No. of Line wires			2	3	3	3	3	4	5	5
Wire Size		Length								
1.7/2.5mm (Green only)		25m	✓	✓	✓	✓				
		10m	✓	✓	✓	✓				
2.24/3.15mm 13.5/10.5g		25m	✓	✓	✓	✓				
		12.5m					✓	✓	✓	✓
2.5/3.55mm 12/9.5g		12.5m	✓	✓	✓	✓	✓	✓	✓	✓
3.0/4.0mm 10.5/8g		12.5m	✓	✓	✓	✓	✓	✓	✓	✓
3.55/4.75mm 9.5/6.5g		12.5m	✓	✓	✓	✓	✓	✓	✓	✓

Suggestions for use:

2.5mm galvanized and 1.7/2.5mm are suitable for general domestic, 2.24/3.15 for site compounds and tennis courts - 2.75m high
Galvanized is best for dogs, 2.5mm for most breeds, but 3mm should be used for the stronger and larger breeds
For heavy industrial use 3mm or 3.5mm galv. or PVC coated, 2.5/3.55mm, 3.0/4mm or 3.5/4.75mm according to situation
40mm and 45mm mesh are available as a special in some heights and gauges

Register on the website to gain access to Q40 specification documents and CAD drawings.

A fully made to measure service is available. All Jacksons fencing systems and gates maybe designed and manufactured to suit site conditions.

Jacksons Fencing Stowting Common Ashford Kent TN25 6BN UK

T: +44 (0) 1233 750 393 F: +44 (0) 1233 750 403

E: sales@jacksons-fencing.co.uk W: jacksons-fencing.co.uk



Jacksons
Quality that lasts
Fine Fencing, Gates and More