

Slotted Jakposts & Square Posts

We manufacture a wide range of fence posts to suit our fence panels and trellis. Slotted Jakposts® are our most popular post option. Available in standard and heavy duty inters, ends, and corners, panels simply slide into posts and fit snugly to stop rattling, and can be securely fixed with screws. New for 2022, our angled slotted fence posts allow corners between 30-45 degrees, adding another option for gardens without sharp 90 degree corners.



Jakposts are 95mm x 98mm, planed finish with two 54mm x 25mm slots for panels. All panels slot easily into position as shown here.

Installation instructions for most of our products are available from our website: www.jacksons-fencing.co.uk. Alternatively, we can supply you with a copy on request.

We have listed below some of the many benefits to using Jakposts:

- Jakcure® treated softwood guaranteed for 25 years.
- Environmentally friendly.
- Jakposts reduce damage caused by wind movement when panels are screwed to posts.
- Unlike concrete posts, there is no risk of frost damage, cracks or chips.
- Easy to carry and lighter than concrete posts.
- More supportive than square section posts, avoids gaps between panels and posts.
- Stainless steel nails used throughout.
- More natural appearance than concrete posts.

NEW Angled Fence Posts

Our angled slotted Jakpost® has been designed to help with those tricky fence runs.

Not every garden or fence run is straight or every corner 90 degrees. Therefore, we have designed and manufactured an angled fence post allowing a change of direction between 30 to 45 degrees.

Only supplied in 2.7m but can be cut to size on site to suit lower fence heights.

We generally recommend that all posts should be set in concrete at a minimum 0.60m into the ground. Please ask for advice when sizing gate posts.

Square Section Panel Posts

Planed finish (not slotted). These are standard square section posts without the unique slot that our superior slotted Jakposts have. It is advisable to fix panels to posts with Jakclips when using standard posts. See page 153.

Recommended Fixings

We recommend using 6 screws per panel or 12 per panel if using capping rails plus an additional 4 per gravel board. 60mm, stainless steel, self-drilling countersunk screws are available in packs of 100 or 200 to secure panels to posts. Panels should be screwed to the posts to secure the fence run.

- Stock items
- Check for availability

Slotted Jakposts

Posts are 100mm x 100mm with two 54mm x 25mm slots for panels.

Fence Height	Post Height	Intermediate Posts		Corner Posts		End Posts		Angled posts	
		Ref		Ref		Ref		Ref	
0.60m	1.06m	756200 ●		756300 ●		756100 ●			
0.90m & 0.75m	1.50m	667200 ●		667220 ●		668200 ●			
1.05m & 1.20m	1.80m	667300 ●		667330 ●		668300 ●			
1.35m & 1.50m	2.10m	667400 ●		667440 ●		668400 ●			
1.65m & 1.80m	2.40m	667500 ●		667550 ●		668500 ●			
2.00m	2.70m	667800 ●		667880 ●		668800 ●		667881NC ■	

* Angled posts are only supplied in 2.7m but can be cut to size on site to suit lower fence

Heavy Duty Jakposts

Posts are 120mm x 124m with two 54mm x 25mm slots for panels.

	Post Height	Intermediate Posts		Corner Posts		End Posts	
		Ref		Ref		Ref	
*Posts are intended to be used for more varied locations and fences of extended height.	2.70m	669000 ●		669010 ●		669011 ●	
	3.00m	669100 ●		669110 ●		669111 ●	
	3.30m*	669200 ●		669220 ●		669222 ●	
	3.60m*	669300 ●		669330 ●		669333 ●	
	3.90m*	669400 ●		669440 ●		669444 ●	

Heavy Duty Square Posts

Size: 91mm x 91mm (planed dimension before treatment) Jakcure® treated posts for hanging light gates etc.

	Post Height	Ref
	1.20m	641100 ■
	1.50m	641200 ●
	1.80m	641300 ●
	2.10m	641400 ●
	2.40m	641500 ●
	2.70m	641600 ●
	3.00m	641700 ●
	3.30m	641800 ●
Locations with strong winds require stronger posts or for them to be dug deeper into the ground - if you have any queries please ask for advice.	3.60m	641900 ●

Standard Square Posts

Size: 70mm x 70mm (planed dimension before treatment)

Fence Height	Post Height	Ref
0.60m	1.20m	640100 ■
0.90m	1.50m	640200 ●
1.20m	1.80m	640300 ●
1.50m	2.10m	640400 ●
1.80m	2.40m	640500 ●
2.10m	2.70m	640600 ●

Screws

	Ref
Stainless Steel Self-Drilling Countersunk Torx Head Screw Pack of 200 60mm	809900 ●
Stainless Steel Self-Drilling Countersunk Torx Head Screw Pack of 100 60mm	809911 ●

Mi-T® Metal Garden Fence Posts

Our Mi-T® post is a modern, secure, and easy to maintain galvanised steel fence post suitable for use with our framed timber fence panels. Manufactured using high quality galvanised steel in the UK with a contemporary slimline design shaped like a ‘T’, these metal posts will not rot or rust and are guaranteed for 25 years. Their innovative design means they are virtually invisible from the front of the fence providing a contemporary, seamless finish in any garden.



Mi-T® Garden Fence Posts are 100% recyclable and offer a sustainable alternative to concrete posts. The ‘T’ shape allows Mi-T to be used as inter and corner posts.

Mi-T® is available in galvanised finished or powder coated Anthracite grey.


Designed for use with our 1.83m high framed panels and gravel board. Our framed panels are Tongue & Groove Effect, Venetian, Hit & Miss, Woven, Aran, Louvre, Urban and Premier Trellis.

Mi-T® Post Specification
Post Length: 2.7m to install 1.83m panel with gravel board
Steel Thickness: 6mm
50 x 50mm ‘T’ design
Hot Dip Galvanised to BS EN 1461 as standard

Mi-T® Posts

	Post Height	Ref
Galvanised Finish	2.70m	669990BM
Powder Coated Anthracite	2.70m	669991BM

Mi-T® Post Timber Cover Board	Ref
Timber cover board to hide visible side of galvanised Mi-T Post.	669900



Our fence post feet offer an alternative to digging, when installing fencing on existing hard surfaces, such as concrete. With two options available for use with our Mi-T® post and Jakpost®, the feet are specially made to fit securely and are bolted down to concrete.



Digging a hole is not always possible, therefore we have produced a version of our Mi-T® post that includes a foot, allowing the post to be installed on a secure hard surface such as concrete.

Mi-T® Post Foot	Post Height	Ref
Galvanised post with foot	1.98m	669905BM ●
Anthracite post with foot	1.98m	669906BM ●

Our strong galvanised Jakpost® foot allows an intermediate standard slotted Jakpost® to be installed on a secure hard surface such as concrete. (Not for use with heavy duty slotted Jakposts®). When fence panels are installed into the slots, most of the bracket and fixings attached to the post are hidden.

When using Slotted Jakpost® feet, posts may need to be cut to length. The cut down post should be coated with Jakcure® cut treatment and the cut end of the post should be installed at the top.



Mi-T® Post Cover Boards can be used to cover the rear side of a galvanised Mi-T®



Due to the erratic price changes in raw material, we have temporarily removed prices from our Good Fencing Guide.

To see our latest prices, view our website by scanning the QR code.

Slotted Jakpost® Foot	Ref
Galvanised slotted post foot	669901BM ●



We have created this product due to frequent requests and while it may save time and make installations easier, every site and application is unique and this product may not be suitable. We take no responsibility for the structure and integrity of the surface the posts are fixed to and the choice of suitable fixings. We cannot accept any responsibility for the strength or durability of the fixing method, or the surface or wall it is fixed to, due to external factors such as wind loads and weathering of the surface or wall, or damage by force from vehicles, intruders climbing, etc.

Gravel Boards

Gravel boards are important in ensuring your fencing stays in good quality condition. Our gravel boards are made from a specific type of timber, which is different to the timber we use for our fencing and is Jakcure® treated specifically for constant ground contact which is integral to ensure we can guarantee our fencing for 25 years.



Due to the erratic price changes in raw material, we have temporarily removed prices from our Good Fencing Guide.

To see our latest prices, view our gravel boards on our website by scanning the QR code.

Gravel boards are also used to raise panels off the ground, give a fence extra height and add a finishing touch to a well put together run of fencing. All timber used throughout is premium quality Jakcure® treated softwood, guaranteed for 25 years.



Jacksons Supply Two Types of Standard Gravel Board:

The first is a gravel board for use with our slotted Jakposts. This version includes two spacer blocks that prevent the gravel board from movement when installed in the slotted posts. The spacer blocks can be purchased separately if spares are required (667601). We recommend gravel boards are screwed into position to prevent any movement.

The second gravel board type we offer is a 2.40m long x 140mm x 25mm (230700) typically used with Traditional Fencing such as Traditional Featherboard. This version will not work with our slotted Jakpost system.

When using two gravel boards to increase the height of a fence, the boards should be held together with a 600mm x 50mm x 50mm (644400) support post to prevent any distortion. This should be placed centrally and driven into the ground with the gravel boards screwed to it. Gravel boards are not intended to retain earth on one side of the fence without additional support.

To meet the conditions of the 25-year Jakcure® guarantee, gravel boards are required where panels are in contact with the ground and any timber cut on site must be treated with Jakcure® Cut Treatment, see page 53.

Gravel Boards	Ref
For use with slotted Jakpost - 1.83m long. 140mm x 28mm with 22mm packers	667600 ●
Not for use with slotted Jakpost - 2.40m long. 150mm x 25mm	230700 ●

Please note: for our Metro gravel boards see page 29.

Hedgehog Friendly Gravel Boards

In response to learning about the decline in hedgehog numbers in the UK - it has been estimated that the current population is down by half since 2000 according to a report published in The Guardian (2018) - Jacksons introduced a hedgehog friendly gravel board for use with Slotted Jakposts (shown above). We have been delighted with the response from the public and wildlife organisations to our raising awareness of this problem and offering a simple solution that allows hedgehogs to roam freely between gardens.

We offer a hedgehog friendly gravel board for use with Jakposts (667610) with a hole at one end, large enough to allow hedgehogs free passage and a reinforcing strip along the top of the board to ensure strength is retained. For more info about the plight of the Hedgehog, visit our website and search for 'Help the Hedgehogs'.

Hedgehog Gravel Boards	Ref
For use with slotted Jakpost - 1.83m long. 140mm x 28mm with 22mm packers	667610 ●

For a hedgehog friendly version of the Traditional Fencing (non-panel) gravel board, we suggest customers cut the gravel board on site and by using a small peg to support the fence rail, as shown in the photo. The support pegs are also used to prevent gravel boards distorting when more than one is used to increase fence height.

Support Peg	Ref
600mm x 50mm x 50mm	644400 ●

● Stock items

Capping Rails Finials & Post Caps

Post Caps, Finials and Capping Rails all add the final touches to a well put together run of fencing.



Some people may think a post without a Cap or Finial looks unfinished, you can judge this for yourself, the top photo on the right shows Ball Finials on the posts, which punctuate the curves of the Trellis Topper panels.




The photo above shows a single Featherboard panel which has been finished with a capping rail, running flush with the post and panel tops to give a crisp, contemporary look.

We offer a selection of Post Caps, Finials and Capping Rails, all manufactured from superior quality Jakcure® treated softwood, and all guaranteed for 25 years.

Standard Capping for Panels	
Planned timber with 2 rounded edges	Ref
1.88m x 120mm x 20mm	667700 ●
2.00m x 120mm x 20mm (for use at ends & corners)	667772 ●

Heavy Duty Capping Rail	
For intermediate slotted posts	Ref
1.900m x 145mm x 35mm	667700H ■
For end and corner slotted posts	
1.985m x 145mm x 35mm	667770H ■

Standard Capping for Panels




The first design is for use with standard slotted and square posts and is a flat style capping for fence panels, made from smooth planned timber with rounded edges. Use code 667700 for capping to be used between intermediate posts. Use code 667772 for capping to be used with end and corner posts.

Note: If you prefer capping to run over the tops of the posts then please use our standard panel capping.

Note: This capping should not be used if you want a totally flat finish where the tops of the post finish in line with the top of the panel.

Capping rail for use with intermediate slotted posts	Ref
1.88m x 120mm x 20mm	667700 ●



Jakcure® Cut Treatment

Where cutting or drilling treated timber cannot be avoided, always use Jakcure® Cut Treatment to ensure no timber is left untreated and the conditions of the 25-year Jakcure® guarantee are met. Read the instructions carefully.

	Ref
500g bottle	131212 ●

● Stock items ■ Check for availability



Two-way chamfered capping

1.84m x 70mm x 26mm

Ref

667778



Post Caps and Finials (shown left from A - K)

Our range includes standard flat square post caps that are a simple finish to the top of a post, alternatively, our simple half round version will give the post a clean domed top. We also offer Decorative Ball and Acorn Finials which come complete with square cap.



Style - All sizes nominal	Ref
A: for use with 75mm x 75mm posts	640900 ●
B1: for use with 100mm x 100mm posts	641000 ●
B2: for use with 125mm x 125mm posts	640660 ●
C: for use with 100mm x 100mm posts	668000 ●
D: for use with 75mm x 75mm posts	645400BM ●
E: for use with 75mm x 75mm posts	645600BM ●
F: for use with 100mm x 100mm posts	645700BM ●
K: for use with 100mm x100mm posts	645880BM ●