



Shows heavy bottom rail pair of Entrance gates, prior to automation.



Entrance Gates for the drive or field



Entrance gates are designed with a heavy top rail over the entire width for extra strength. All timber used throughout is superior quality planed Jakcured softwood guaranteed for 25 years. Rail and brace crossings are bolted with stainless steel bolts. The gates are cross braced for extra strength and all joints are morticed and tenoned.

Gates are 1.2m high except for the hanging stile which is 1.5m. Hanging Stile 125 x 75mm, Slam Stile 75 x 75mm, Top Rail is 100 x 75mm and under rail and cross braces 75 x 25mm. Supplied in natural Jakcured finish. As standard larger sizes are right hand hanging, smaller sizes are left hand hanging, see below for details.

Entrance Gates - Narrow - Specification (0.9 - 1.5m wide)

Single cross braced. Gates are 1.2m high except for the curved hanging stile which is 1.5m and slam stile 75 x 75mm. Top rail is 100 x 75mm. Left hand hanging when viewed from the front. (opposite hanging available at no additional cost).

Length	Ref
0.9m	262800 ■
1.2m	262900 ■
1.5m	263000 ○

Additional items required for hanging a single narrow entrance gate; Galvanised fittings, Hinge set, Spring catch, anti-lift device, padlock & two 2.1m, 150 x 150mm gate posts. **TRHSSLN**

Entrance Gates - Wide Specification (1.8 - 3.6m wide)

Additional items required for hanging a single wide entrance gate; Galvanised fittings, Hinge set, Spring catch, anti-lift device, padlock & 2.1m, 175 x 175mm Hanging post and 2.1m, 150 x 150mm Shutting post. Right hand hanging when viewed from the front (opposite hanging available at no additional cost).

Length	Ref
1.8m	263100 ○
2.1m	263200 ○
2.4m	263300 ○
2.7m	263400 ○
3.0m	263500 ■
3.3m	263600 ○
3.6m	263700 ■

hanging system for:

Single wide and narrow entrance gate **TRHSSL**
 Double wide entrance gate (includes loop over, drop bolt & centre gate stop etc.) **TRHSDL**

Safety notes - please read:

If you are considering automating these gates please ask for advice. For any Jacksons five bar gates to be retro-fitted for automation we insist that an extra heavy bottom rail across the width of the gate is fitted to avoid twisting.

It is also essential for any swing gates that are automated to be fitted with finger guards. See residential auto-gates pages for more info. All catches and latches are for adult operation only - children must be supervised.



Uni-Gates for the drive or field



Our Uni-Gates are called this as they are 'Universal' which means they can be hung as right or left handed. They are designed with a heavy top rail over the entire width for extra strength. All timber used throughout is superior quality planed Jakcured softwood guaranteed for 25 years. Top bars are chamfered and both hanging and slam stiles are drilled to allow gates to be hung on the left or right. Rail and brace crossings are bolted with stainless steel bolts. The gates are cross braced for extra strength and all joints are morticed and tenoned.

Uni-Gates

Specification (0.9 - 4.2m wide)

Gates are 1.27m high overall. Top rail 100mm x 75mm, under rail and cross braces 75 x 25mm. Hanging and slam stiles (rounded top) 100 x 75mm, with both stiles drilled to allow gates to be hung on the left or the right. Supplied in natural Jakcured finish.

Narrow Uni-Gates

Length	Ref.
0.9m*	255000 ●
1.05m*	255090 ●
1.2m	251100 ●
1.5m	255200 ●
1.8m	255300 ●
2.1m	255400 ●

Narrow Uni-Gates only-
Left handed bracing when
viewed from front, opposite
hanging available at no
extra cost. If you require a
matching pair, please ask.

Wide Uni-Gates

Length	Ref
2.4m	255500 ●
2.7m	256600 ●
3.0m	257700 ●
3.3m	258800 ●
3.6m	259900 ●
3.9m	256000 ●
4.2m	256100 ●

*with a single brace

Additional items required to hang single Uni-Gate; Galvanised fittings, Hinge set, Spring catch, anti-lift device, padlock 2.1m, 175 x 175mm Hanging post & 2.1m, 150 x 150mm Shutting post. Please see following pages. Ref TRHSSL



Shows a narrow Uni-Gate with its characteristic cross braces.

Safety notes - please read:

If you are considering automating these gates please ask for advice. For any Jacksons five bar gates to be retro-fitted for automation we insist that an extra heavy bottom rail across the width of the gate is fitted to avoid twisting.

It is also essential for any swing gates that are automated to be fitted with finger guards. See residential auto-gates pages for info. All catches and latches are for adult operation only - children must be supervised.

● STOCK ITEMS