





Panels shown with optional capping rails.

# Paliframe panel



Paliframe is a variation on our classic Palisade panel. Alternate pales have been cut at an angle to create a very pleasing decorative effect. They are ideal for creating light and airy gardens as they allow sunlight through and offer less wind resistance than solid panels. Paliframe is unique to Jacksons. Its original good looks have captured the imagination of not only residential customers, but also garden designers.

Paliframe panels are manufactured from superior quality, planed finish Jakcured softwood, guaranteed for 25 years and are framed for use with our slotted Jakposts, see pages 40 - 41.

Stainless steel nails are used throughout for longer life.

For matching gates please see pages 56 - 60.

Gravel boards need to be used when panels are in contact with the ground as part of the 25 year Jakcure guarantee conditions, see pages 42 - 43.

Paliframe Panels (1.83m wide) are only offered at 1.83m high

Height	Ref
1.83m	657500 ●

If you have to cut down a panel on site then use the following kit reference. Always use Jakcure End Grain Treatment on cut timber, see page 45.

Height	Ref
1.83m	630400K ●

paliframe panels







# Chilham panel



It has long been a challenge to design a fence that can look equally good on both sides. Usually you have to have a rail or two to strengthen the fence across the horizontal and to attach the pales to. We have managed 'good both sides with this design that is unique to Jacksons. It was developed so we can offer you a premium panel that has no rails on either side to spoil either yours or your neighbour's view.

The Chilham has an attractive 'panelled' appearance due to its construction, it is aesthetically pleasing and sturdy, and looks as at home in a traditional English cottage garden as it does in a sleek, modern urban garden.

Four panel heights available, all at 1.83m wide. Constructed from Jakcured softwood, Chilham panels are framed for use with our slotted Jakposts, see pages 40 - 41. Stainless steel nails are used throughout for longer life.

Matching gates available, see pages 56 - 60. Gravel boards need to be used when panels are in contact with the ground as part of the 25 year Jakcure guarantee conditions, see pages 42 - 43.

## Chilham Panels (1.83m wide)

Height	Ref
0.91m	656000 ■
1.22m	656100 ■
1.52m	656200 ●
1.83m	656300 ●

If you have to cut down a panel on site then use the following kit references. Always use Jakcure End Grain Treatment on cut timber, see page 45.

Cut width kit	Ref
0.91m	656000K ●
1.22m	656100K ●
1.52m	656200K ●
1.83m	656300K ●

Please note: some timber products will take a while to dry out after the Jakcure process and natural shrinkage can occur. To prevent unstained timber becoming visible, we recommend not staining products until they have had a prolonged period of dry weather to fully dry out.







# Woven panel



Woven panels look good from all angles.

Belonging to Jacksons premium panels range, Woven are a modern panel designed with traditional inter-woven styles of fencing in mind. As with all Jacksons' panels, they are constructed from Jakcured pressure treated softwood and framed for use with slotted Jakposts, making them far stronger than old fashioned versions of this type of fence panel.

The Woven fence panel may look like an old style inter-woven panel, but there the resemblance ends; the horizontal timbers are substantial pieces of smooth Jakcured treated softwood, measuring 38mm high by 7mm deep, that will stay strong, maintaining the structural integrity of the panel, and all fitted in to a strong frame. There are no unsightly rails to ruin the appearance on one side of the panel, so you and the neighbours are both winners.

Another benefit is you get amazing dappled light and shade effects when sunlight shines through the panel, and wind resistance is lowered due to air being able to move through the spaces between the slats. Woven panels offer a less see-through option for more privacy - some trellis and semi solid panels can allow a lot of light through, but that also means they can be seen through quite easily too.

Constructed from Jakcured softwood, Woven panels are framed for use with our slotted Jakposts, see pages 40 - 41. Stainless steel nails are used throughout for longer life.

Matching gates available, see pages 56 - 60. Gravel boards need to be used when panels are in contact with the ground as part of the 25 year Jakcure guarantee conditions, see pages 42 - 43.

## Woven Panels (1.83m wide)

Height	Ref
0.91m	656700 ■
1.22m	656800 ■
1.52m	656500 ●
1.83m	656600 ●

If you have to cut down a panel on site then use the following kit reference. Always use Jakcure End Grain Treatment on cut timber, see page 45.

	Ref
Cut width kit	656600K ●

Panels shown with optional capping rails.

woven panels





Panels shown with optional capping rails.





# Canterbury Combi panel



These new panels are a hybrid of two popular Jacksons' products: the lower three quarters of the panel is made up of premium tongue and groove effect boards turned horizontally and the ever-popular Venetian on the top quarter. All is surrounded by a sturdy frame.

They have the sleek modern feel of Jacksons Venetian, but they have the added benefit of extra privacy and protection from the wind that some customers may prefer, with the solid tongue and groove effect lower part of the panel.

Please note the Venetian pale spacing is slightly different on these panels compared to the standard Venetian panel.

Available panel height is 1.83m x 1.83m wide.

Constructed from Jakcured softwood, Woven panels are framed for use with our slotted Jakposts, see pages 40 - 41. Stainless steel fixings are used throughout for longer life.

Matching gates available, see pages 56 - 60. Gravel boards need to be used when panels are in contact with the ground as part of the 25 year Jakcure guarantee conditions, see pages 42 - 43.

Canterbury Combi Panels (1.83m wide)

Height  
1.83m

Ref  
658000 ●

If you have to cut down a panel on site then use the following kit reference. Always use Jakcure End Grain Treatment on cut timber, see page 45.

Cut width kit  
Ref  
657400K ●









# Jaktop panels



Jaktop graces many a front garden in suburban, as well as rural areas, and is a popular alternative to the very traditional Palisade or picket style front garden fence.

The crossed half round timber pales give the panels a very distinctive look and criss-cross pattern. Jaktop Panels come complete as a fixed panel with rails, to be used with slotted Jakposts, see pages 40 - 41.

Panels can be installed clear of the ground, or gravel boards need to be used when panels are in contact with the ground as part of the 25 year Jakcure guarantee conditions, see pages 42 - 43.

Manufactured from superior quality, Jakcured softwood, guaranteed for 25 years. All fittings and fixings throughout are stainless steel for longer life.

## Jaktop Panels Specification

Jaktop Panels are made from tough 50 x 22mm half round timber, backed by two rails for the 0.8m & 1.2m & three rails for 1.8m panels. All panels are 1.83m wide. Supplied in a natural Jakcured finish.

Matching gates are available, see pages 56 - 60.

Available in 1.83m wide x 1.83m high, other sizes are also available but are made to order. The panels can be cut to width on site, with the original side batten being re-used in the new situation. Always use Jakcure End Grain Treatment on cut timber, see page 45.

Jaktop Panels - shown below  
(1.83m wide, for use with slotted posts)

Height	Ref
0.86m	600600 ■
1.2m	600700 ■
1.8m	600800 ■

■ CHECK FOR AVAILABILITY