



Panels shown with recommended capping rails.



The Aran panel is one of our latest ‘good-both-sides’ designs and features slats of different depths, intertwined to create a unique and attractive traditional style.

The interwoven design not only creates subtle light and shade effects in your garden but also means that both you and your neighbour benefit from the best looking side of the fence with almost as much privacy as you would expect from a solid panel.

Aran panels are designed for use with our slotted Jakposts, see pages 46 - 47, and manufactured from superior quality, planed finish Jakcure® treated softwood, guaranteed for 25 years.

Stainless steel fixings are used throughout for longer life.

Available as a 1.83m high by 1.83m wide panel.

Our Woven or Brook gates complement this panel (pages 62 - 66).

To meet the conditions of the 25-year Jakcure® guarantee, gravel boards are required where panels are in contact with the ground, see pages 48 - 49, and any timber cut on site must be treated with Jakcure® End Grain Treatment, see page 51.

Please note: There is no need to apply any further timber protection treatment to your Jacksons Jakcure® treated product. Some customers might want to add colour to their Jacksons products. In these cases, please be aware that timber will naturally take a while to dry, during which, natural shrinkage can occur, so we recommend that you don’t apply any colour coatings until the timber is fully dry and stable.

Aran Panels (1.83m x 1.83m wide only).

Height Ref

1.83m 656618 ○

If you have to cut down a panel on site then use the following kit reference. Always use Jakcure® End Grain Treatment on cut timber, see page 51.

Cut width kit

Ref 656600K ●

● STOCK ITEMS ○ MADE TO ORDER (CANNOT BE CANCELLED ONCE ORDERED)



Mitre Panels



The Mitre panel is a new addition to our range. Inspired by our traditional Palisade fence panels, the Mitre panel features 45mm x 16.5mm redwood pales with an elongated curved top for a traditional picket design with a little more elegance, making it equally at home in a rural or urban setting.

It’s perfect for front gardens or situations where natural light takes priority over privacy.

Mitre panels are designed for use with our slotted Jakposts, see pages 46 - 47, and manufactured from superior quality, planed finish Jakcure® treated softwood, guaranteed for 25 years.

Stainless steel fixings are used throughout for longer life.

Available as a 1.0m or 1.2m high by 1.83m wide panel.

To meet the conditions of the 25-year Jakcure® guarantee, gravel boards are required where panels are in contact with the ground, see pages 48 - 49, and any timber cut on site must be treated with Jakcure® End Grain Treatment, see page 51.

Please note: There is no need to apply any further timber protection treatment to your Jacksons Jakcure® treated product. Some customers might want to add colour to their Jacksons products. In these cases, please be aware that timber will naturally take a while to dry, during which, natural shrinkage can occur, so we recommend that you don’t apply any colour coatings until the timber is fully dry and stable.

Mitre Panels (1.83m wide).

Height	Ref	Gate Options	
1.0m	229010	0.95 RH Gate	229100
1.2m	229012	0.95 LH Gate	229110
		1.15 RH Gate	229200
		1.15 LH Gate	229220

MADE TO ORDER (CANNOT BE CANCELLED ONCE ORDERED)



Panels shown with recommended capping rails.



Storm Panels

The Storm panel is the most recent addition to the ‘good-both-sides’ Hit and Miss family.

Originally designed to provide a sturdy demarcation fence for use in locations exposed to high winds where solid panels or lighter weight palisade designs are inappropriate. This ‘good-both-sides’ fence is popular choice in many settings.

Constructed using substantial 100mm x 25mm Jakcure® treated softwood slats on both sides of the panel with an over-lap which allows air and light to pass through, but with restricted visibility through the panel.

Storm panels are designed for use with our slotted Jakposts, see pages 46 - 47, and manufactured from superior quality, planed finish Jakcure® treated softwood, guaranteed for 25 years.

Stainless steel fixings are used throughout for longer life. Available as a 1.2m high by 1.83m wide panel. For garden gate options which complement this panel see pages 62 - 66.

The Storm panel comes with a built-in gravel board. Any timber cut on site must be treated with Jakcure® End Grain Treatment, see page 51.

Please note: There is no need to apply any further timber protection treatment to your Jacksons Jakcure® treated product. Some customers might want to add colour to their Jacksons products. In these cases, please be aware that timber will naturally take a while to dry, during which, natural shrinkage can occur, so we recommend that you don’t apply any colour coatings until the timber is fully dry and stable.

Panels can be cut to a desired width on site.

Storm Panels (1.83m wide).

Height	Ref
1.2m	658312 ○

○ MADE TO ORDER (CANNOT BE CANCELLED ONCE ORDERED)



Panels shown with recommended capping rails.



Metro Panels

One of our newest additions to the premium slatted style range is the Metro Panel, which is a contemporary slatted panel offering a sleek alternative to traditional fencing. Metro is a semi-solid decorative panel, ideal for creating a lighter garden where privacy is not an issue.

This panel has been designed with an urban motif in mind, featuring singular pales, similar to our Venetian. The key difference is that the fence posts are less visible, meaning that, when installed, the panel will appear as continuous slats, rather than a run of individual panels. This style of panel has been designed to create a feeling which makes gardens appear longer. Nevertheless, this panel has the ability to modernise and blend into country gardens with its contemporary design.

Constructed from Jakcure® treated softwood, the Metro Panels use our 91mm x 91mm square posts, stainless steel nails are used throughout for longer life. Constructed using 45mm x 16mm horizontal slats with a gap between the slats of approximately 30mm (which is larger than standard Venetian).

Venetian gates will complement this panel perfectly, see pages 62 - 66.

Gravel boards need to be used when panels are in contact with the ground as part of the 25 year Jakcure® guarantee conditions. This panel uses a unique gravel board (see below).

0.9m high - 12 pales 45 x 16.5 (Venetian section).
0.6m high - 8 pales 45 x 16.5 1.83m wide.
2 no. vertical battens 45mm x 34mm, 2no. 45mm x 16.5mm.

Please ask for advice when installing panels into a corner as internal battens will be required.

Metro Panels (1.83m wide)		Gravel Board Ref
Height	Ref	
0.607m	657906 ○	667620 ○
0.907m	657909 ○	
Cut width kit		Metro Panel Internal Corner Batten
0.607m	657906K ○	1.8m long - 667300C
0.907m	657909K ○	

○ MADE TO ORDER (CANNOT BE CANCELLED ONCE ORDERED)



Chilham Panels



It's a challenge to design a solid timber fence that looks equally good on both sides. However, our Chilham panels manage just that, in a unique design, free from horizontal rails that could spoil either yours or your neighbour's view.

The Chilham presents an attractive 'panelled' appearance and due to its construction, is sturdy too. It looks equally at home in a traditional English cottage garden setting as it does in a sleek urban setting.

Chilham panels are designed for use with our slotted Jakposts, see pages 46 - 47 and manufactured from superior quality, planed finish Jakcure® treated softwood, guaranteed for 25 years.

Stainless steel fixings are used throughout for longer life.

Four panel heights available, all at 1.83m wide and for matching gates see pages 62 - 66.

To meet the conditions of the 25-year Jakcure® guarantee, gravel boards are required where panels are in contact with the ground - pages 48 - 49, and any timber cut on site must be treated with Jakcure® End Grain Treatment, see page 51.

Please note: There is no need to apply any further timber protection treatment to your Jacksons Jakcure® treated product. Some customers might want to add colour to their Jacksons products. In these cases, please be aware that timber will naturally take a while to dry, during which, natural shrinkage can occur, so we recommend that you don't apply any colour coatings until the timber is fully dry and stable.

Chilham Panels (1.83m wide)

Height	Ref
0.91m	656000 ●
1.22m	656100 ●
1.52m	656200 ●
1.83m	656300 ●

If you have to cut down a panel on site then use the following kit references. Always use Jakcure® End Grain Treatment on cut timber, see page 51.

Cut width kit	Ref
0.91m	656000K ●
1.22m	656100K ●
1.52m	656200K ●
1.83m	656300K ●

● STOCK ITEMS



Panels shown with optional capping rails.

Woven Panels



Part of our premium ‘good-both-sides’ panels range, Woven is designed with the traditional inter-woven styles of the past in mind. As with all Jacksons panels, they are constructed from Jakcured pressure treated softwood and framed for use with slotted Jakposts, making them far stronger than traditional versions of this style of fencing.

Woven panels feature substantial 38mm x 7mm pales that maintain the structural integrity of the panel which are then fitted into a strong frame. There are no unsightly mid rails, so you and your neighbours are both winners.

Other benefits of our Woven panels are that it creates amazing dappled light and shade effects and, while it provides a high level of privacy, wind resistance is lowered due to air being able to pass through the spaces between the slats.

Woven panels are designed for use with our slotted Jakposts, see pages 46 - 47, and manufactured from superior quality, planed finish Jakcure® treated softwood, guaranteed for 25 years. Stainless steel fixings are used throughout the fencing for longer life.

Four panel heights available, all at 1.83m wide along with a panel width cut-down kit.

For matching gates please see pages 62 - 66.

To meet the conditions of the 25-year Jakcure® guarantee, gravel boards are required where panels are in contact with the ground, see pages 48 - 49, and any timber cut on site must be treated with Jakcure® End Grain Treatment, see page 51.

Please note: There is no need to apply any further timber protection treatment to your Jacksons Jakcure® treated product. Some customers might want to add colour to their Jacksons products. In these cases, please be aware that timber will naturally take a while to dry, during which, natural shrinkage can occur, so we recommend that you don’t apply any colour coatings until the timber is fully dry and stable.

Woven Panels (1.83m wide)

Height	Ref
0.91m	656700 ■
1.22m	656800 ■
1.52m	656500 ●
1.83m	656600 ●

If you have to cut down a panel on site then use the following kit reference. Always use Jakcure® End Grain Treatment on cut timber, see page 51.

	Ref
Cut width kit	656600K ●

● STOCK ITEMS ■ CHECK FOR AVAILABILITY



Panels shown with recommended capping rails and our latest 'frameless design' for a more continuous look.

Canterbury Combi Panels



These premium contemporary panels combine two of Jacksons’ most popular products: horizontal Tongue and Groove with our ever-popular Venetian, using handcrafted pressure treated timber.

Canterbury Combi lends a sleek, modern and linear look to any garden, with the added benefits of privacy and protection from the wind that some customers may prefer.

Please note the slatted pale spacing is different on these panels when compared with a standard Venetian panel.

Canterbury Combi panels are designed for use with our slotted Jakposts, see pages 46 - 47, and manufactured from superior quality, planed finish Jakcure® treated softwood, guaranteed for 25 years and fitted with stainless steel fixings throughout for longer life.

Available panel size is 1.83m high x 1.83m wide along with a panel width cut-down kit.

For matching gates please see pages 62 - 66.

To meet the conditions of the 25-year Jakcure® guarantee, gravel boards are required where panels are in contact with the ground - pages 48 - 49, and any timber cut on site must be treated with Jakcure® End Grain Treatment, see page 51.

Please note: There is no need to apply any further timber protection treatment to your Jacksons Jakcure® treated product. Some customers might want to add colour to their Jacksons products. In these cases, please be aware that timber will naturally take a while to dry, during which, natural shrinkage can occur, so we recommend that you don’t apply any colour coatings until the timber is fully dry and stable.

Please Note: from February 2018 our Canterbury Combi panel has been modified to ensure a contemporary design. Should you require panels pre-February 2018 please do let us know.

Height
1.83m Ref
658018 ●

If you have to cut down a panel on site then use the following kit reference. Always use Jakcure® End Grain Treatment on cut timber, see page 51.

Cut width kit Ref
658018K ●



Jaktop Panels



Our Jaktop panels and gates grace many front gardens in rural and suburban areas and offers a decorative alternative to palisade or picket style fencing.

The criss-crossed pattern constructed using half round timber pales give the panels a very distinctive look while the addition of sturdy rails and vertical end pales create a fixed panel suitable for use with slotted Jakposts, see pages 46 - 47.

Jaktop panels are manufactured from superior quality, Jakcure® treated 50 x 22mm half round softwood pales, backed by two rails and are guaranteed for 25 years. Additionally, Jaktop panels are normally mounted 50mm clear of the ground.

Stainless steel fixings are used throughout for longer life.

Available in two heights at 1.83m wide. Jaktop panels can be cut to width on site, with the original side batten re-used.

For matching gates please see pages 62 - 66.

To meet the conditions of the 25-year Jakcure® guarantee, gravel boards are required where panels are in contact with the ground - pages 48 - 49. Any timber cut on site must be treated with Jakcure® End Grain Treatment, see page 51.

Please note: There is no need to apply any further timber protection treatment to your Jacksons Jakcure® treated product. Some customers might want to add colour to their Jacksons products. In these cases, please be aware that timber will naturally take a while to dry, during which, natural shrinkage can occur, so we recommend that you don't apply any colour coatings until the timber is fully dry and stable.

Jaktop Panels
(1.83m wide - for use with slotted posts)

Height	Ref
0.86m	600600 ■
1.2m	600700 ■

■ CHECK FOR AVAILABILITY