

## Storm Panel

Manufacturer: Jacksons Fencing.  
Web: [www.jacksons-fencing.co.uk](http://www.jacksons-fencing.co.uk).  
Tel: +44 (0)1233 750393.

**Product reference:**

Storm Panel

**Width – As Standard:**

1.83m

**Height:**

1.2m

Pales: 80mm x 15mm slats.

Panel Thickness: 51mm

**Gravel Boards:**

Gravel boards is built into the panel. 140mm added to the height.

**Posts:**

Slotted Jakposts®

**Guarantee:**

All timber used throughout is superior quality Jakcure® treated softwood guaranteed for 25 years.

**Features:**

- All fixings are stainless steel.
- Gravel boards is built into the panel.
- All timber is planed all round.
- Capping Rail is recommended to finish installation.
- Provides a sturdy demarcation fence for use in locations exposed to high winds.

**Gates:**

Our Storm Panel does not have matching gates, but other gate types can be recommended to suit.

Height: N/A

Width: N/A

**Installation**

In accordance to manufacturer's instructions.

The Storm panel is the most recent member of the 'good-both-sides' Hit and Miss family. It was originally designed to provide a sturdy demarcation fence for use in locations exposed to high winds where solid panels or lighter weight palisade designs are inappropriate.

For additional information, please contact Jacksons Fencing. All information within was correct at time of creation. We reserve the right to alter specification without notice.