

Timber Decking



We manufacture three types of timber decking: standard, heavy duty, and slip resistant. Timber decking is versatile and can be used to create functional year-round outdoor surfaces.

- All timber used throughout is superior quality Jakcure® treated softwood guaranteed for 25 years.
- Boards are grooved to aid slip resistance
- Ideal for sloping ground to create usable space
- Choice of balustrades to add a safety demarcation railing to raised decks
- Easy to cut to size and create steps

Specification (dimensions are nominal)

Standard decking board: 3.6m x 100 x 25mm, 2.4m x 100 x 25mm

Heavy duty decking board: 3.0m x 150 x 32mm, 3.6m x 150 x 32mm, 4.2m x 150 x 32mm, 4.8m x 150 x 32mm

Slip resistant heavy duty decking board: 3.6m x 150 x 32mm

Decking joist: 3.00m x 100mm x 50mm, 3.60m x 100mm x 50mm, 3.60m x 150mm x 50mm (thickened)

Decking support post: 0.60m x 100mm diameter, 0.90m x 100mm diameter, 1.20m x 100mm diameter

Decking stringer: 2 tread 850mm long, 3 tread 1200mm long, 4 tread 1530mm long, 5 tread decking stringer (1865mm long) (Please note that stringers should be placed at 450mm centres)

Always use end grain treatment supplied by Jacksons on any cut timber.



Slip resistant decking boards resin and aggregate mixture (grit)



Steps up to a hot tub constructed from decking boards and stringer underneath



Detail of decking board profile with stress relief cuts underneath

View our website for Q40 specification documents, CAD drawings and products available to buy online. A fully made to measure service is available. All Jacksons Fencing systems and gates may be designed and manufactured to suit site conditions. Components may swell by up to 6% in width following the Jakcure® process, which may temporarily affect overall product dimensions.