Uni Gates







Our Uni-Gates are called this as they are 'universal' which means they can be hung as right or left handed. They are designed with a heavy top rail over the entire width for extra strength. All timber used throughout is superior quality planed Jakcure® treated softwood guaranteed for 25 years.

- All timber used throughout is superior quality Jakcure® treated softwood guaranteed for 25 years.
- All fixings are stainless steel.
- Rail and brace crossings are bolted with stainless steel bolts

Specification

Top bars are chamfered and both hanging and slam stiles are drilled to allow gates to be hung on the left or right. Rail and brace crossings are bolted with stainless steel bolts.

The gates are cross braced for extra strength and all joints are morticed and tenoned.

Gate Heights: Gates are 1.27m high overall.

Top rail 100mm x 75mm, under rail and cross braces 75mm x 25mm.

Hanging and slam stiles (rounded top) 100mm x 75mm (nominal sizes), with both stiles drilled to allow gates to be hung on the left or the right. Supplied in natural Jakcure® treated finish.

Gate Widths

0.90m, 1.05m, 1.20m, 1.50m, 1.80m, 2.10m, 2.40m, 2.70m, 3.00m, 3.30m, 3.60m, 3.90m, 4.20m

View our website for Q40 specification documents, CAD drawings and products available to buy online.

A fully made to measure service is available. All Jacksons Fencing systems and gates may be designed and manufactured to suit site conditions.

