

Hit & Miss Panel - Vertical

Jacksons Fencing



Hit and Miss panels are so called because the boards are alternately fixed on the front and the back of the panel with an over-lap to create a stylish Hit and Miss pattern. They are part of our premium 'good-both-sides' range so that both you and your neighbour have the best looking side of the fence, as both sides are the same.

- All timber used throughout is superior quality Jakcure® treated softwood guaranteed for 25 years.
- All fixings are stainless steel.
- Designed for use with slotted Jakposts®.
- Panels have a morticed and tenoned frame for extra strength.
- Hit and Miss panels' design allows some wind and light to pass through. It also allows visibility through the fence at an angle.
- All timber is planed all round.
- Gravel boards are required where panels are in contact with the ground.

Specification

Panel Heights: 0.91m 1.22m 1.52m 1.83m

Panel Width: 1.83m

Framing: 45 x 51mm.

Panel Thickness: 51mm

If you need to reduce the width of a panel on site, a cut down kit is available. Always use Jakcure® End Grain Treatment on any cut timber.

Gates

Gates are Jakcure® treated softwood, right and left hand hanging (when viewed from the outside) as standard designed to match our Hit & Miss Panel - Vertical. Non-standard gates with custom width / heights are available as a special order and are also available as pairs (size restriction applies).

- Elegantly designed to match our Hit & Miss Panel - Vertical.
- Gates are morticed and tenoned frame for extra strength.
- Galvanised ring latches and adjustable hinges.
- All fixings and fittings are galvanised or stainless steel.

Standard Gate Heights: 1.78m to 1.93m (with capping).

Standard Gate Widths: 1m

View our website for Q40 specification documents, CAD drawings and products available to buy online.

A fully made to measure service is available. All Jacksons Fencing systems and gates may be designed and manufactured to suit site conditions.

Note that components can temporarily swell up to 6% in width after our Jakcure® process temporarily affecting the overall product dimensions.

